

DEPOSIT CHUTE SAFE







Features

- Solid steel construction with 12mm steel plate door and 6mm steel plate body reinforced with heavy steel frame all around front edges.
- External hinges with internal pry-resistant dead bolts.
- Drill resistant hardened steel plate to protect lock area.
- Secondary spring-loaded re-locking devices.
- 32mm solid steel bolt work..
- 4 x 15mm bolt holes in base.
- Durable powder coated hammertone finish in Charcoal.
- Safe with electronic digital lock
 - Quality UL listed SecuRAM electronic digital safe lock.
 - Programmable manager code and user code.
 - Errant access lockout feature.
 - Battery compartment is located within the keypad housing.
 - Universal lock footprint for easy lock conversion. Audit trial, time delay, dual control, bluetooth, multi-user, timelock and emergency key override available at an additional cost.

Specifications

Model	Internal	Lock type		External dimensions (mm)			Shelves	Weight	RRP
	compartment	Internal compartment	External	Height	Width	Depth	Oncives	(kgs)	(incGST)
AP-7038SE	NIL	NIL	SecuRam digital lock	700	380	360	1	94	
AP-7038SEK	1	Lever key lock	SecuRam digital lock	700	380	360	1	98	
AP-7038SEE	1	SecuRam digital lock	RecuRam digital lock	700	380	360	1	98	

Depth measurement does not include the handle, keypad or hinges (please allow 50mm). Warranty: 12 month warranty excluding freight and travelling.

The safe pictures shown on this brochure are for illustrative purpose only. Weights and dimensions are approximate. We reserve the right to alter specifications without notice or obligation.

